

Diffused Aeration



AQUA AURA
Leading Technologies

JetFlex® HD 340 Disc Diffuser




JetFlex® HD 340 Disc Diffuser

Dimensions

Diameter total [A] / effective	Installation height above pipe [B]	Overall height [C]	Orifice	Thread
346/295 mm	46 mm	76 mm	10 mm	R 3/4" +1"




Installation drawing



A = 346 mm
B = 46 mm
C = 76 mm

SSOTE and headloss for HD 340 F053A



Perforated area	Air flow rate at standard operating conditions	Max. overload / maintenance air flow rate	Operating mode
0.060 m²	2 - 12 Nm³/h	15 Nm³/h	continuous / intermittent

Connectors to plastic header pipe

	Colour	Permitted wall thickness of header tube	Diameter of straight-drilled hole	Material
Rubber saddle	black	4 - 8 mm	32 mm	EPDM 75 ± 5 Shore A
PVC saddle 90 + 110 mm	grey/white	2 mm	35 mm	PVC
Clamp adapter 90 + 110 mm	black	2 mm	multiple	PP20%GF/SI/VA

Please see our operation manuals for more details.

JetFlex® HD 340 Disc Diffuser


Membrane materials

Material	Techn. standard	EPDM F053A	EPDM F057A	Techn. standard	Silicone
Colour		black	black		green
Plasticiser (%)		28	9		0
Density (g/cm³)	DIN EN ISO 1183-1	1.07	1.06	DIN EN ISO 1183-1	1.17
Tensile strength (N/mm²)	DIN 53504	>10	>8	DIN 53504	>7
Elongation at break (%)	DIN 53504	>450	>300	DIN 53504	>300
Tear strength (N/mm)	DIN EN ISO 34-1 (method A)	>6	>3	DIN EN ISO 34-1 (method B)	>37.7
Hardness (Shore A)	DIN ISO 7619	52 ± 5	60 ± 5	DIN ISO 7619	60 ± 5
Operating air temperature (°C)		5 - 80	5 - 80		5 - 100
Operating water temperature (°C)		5 - 40	5 - 40		5 - 40

Support plates

Material	Colour
PP 30% GF	black

Accessories



Rubber saddle



PVC saddle



Check valve



Clamp adapter with female thread



Clamp adapter without thread

Please see our accessories catalogue for more details.



AQUA AURA
Leading Technologies

Aqua Aura Limited
info@aquaura.net
www.aquaura.net



JÄGER
Umwelt-Technik